

ジグ用ブッシュ定価表

形式 d 内径	SAK(上段)						SBK・BRK(上段)						SCK・CRK(上段)			
	AK(下段)						BK(下段)						CK(下段)			
	φ 長さ	単価	φ 長さ	単価	φ 長さ	単価	φ 長さ	単価	φ 長さ	単価	φ 長さ	単価	φ 長さ	単価	φ 長さ	単価
0.8 ~1.0	6	1,510	8	1,660												
1.1 ~1.5	6	1,210	8	1,320												
1.6 ~2.0	8	1,110 1,010	10	1,210 1,110	12	1,320 1,210	8	1,670 1,510	10	1,820 1,670	12	2,000 1,820	12	2,480 2,250		
2.1 ~3.0	8	990 900	10	1,080 990	12	1,190 1,080	8	1,440 1,310	10	1,580 1,440	12	1,740 1,580	12	1,980 1,800		
3.1 ~4.0	10	880 800	12	960 880	16	1,050 960	10	1,220 1,110	12	1,340 1,220	16	1,480 1,340	12	1,780 1,620	16	1,950 1,780
4.1 ~6.0	10	770 700	12	850 770	16	930 850	10	1,110 1,010	12	1,220 1,110	16	1,340 1,220	12	1,680 1,530	16	1,850 1,680
6.1 ~8.0	12	770 700	16	850 770	20	930 850	12	1,110 1,010	16	1,220 1,110	20	1,340 1,220	16	1,680 1,530	20	1,850 1,680
8.1 ~10.0	12	770 700	16	850 770	20	930 850	12	1,110 1,010	16	1,220 1,110	20	1,340 1,220	16	1,680 1,530	20	1,850 1,680
10.1 ~12.0	16	880 800	20	960 880	25	1,050 960	16	1,220 1,110	20	1,340 1,220	25	1,480 1,340	20	1,780 1,620	25	1,950 1,780
12.1 ~15.0	16	990 900	20	1,080 990	25	1,190 1,080	16	1,330 1,210	20	1,460 1,330	25	1,600 1,460	20	1,980 1,800	25	2,180 1,980
15.1 ~18.0	20	1,110 1,010	25	1,220 1,110	30	1,330 1,220	20	1,550 1,410	25	1,700 1,550	30	1,860 1,700	25	2,280 2,070	30	2,500 2,280
18.1 ~22.0	20	1,220 1,110	25	1,330 1,220	30	1,470 1,330	20	1,770 1,610	25	1,940 1,770	30	2,130 1,940	25	2,820 2,570	30	3,100 2,820
22.1 ~26.0	25	1,400 1,270	30	1,540 1,400	35	1,690 1,540	25	2,110 1,920	30	2,310 2,110	35	2,540 2,310	30	3,240 2,950	35	3,560 3,240
26.1 ~30.0	25	1,520 1,380	30	1,650 1,520	35	1,820 1,650	25	2,340 2,130	30	2,560 2,340	35	2,810 2,560	30	3,870 3,520	35	4,250 3,870
30.1 ~35.0	30	1,870 1,700	35	2,040 1,870	45	2,240 2,040	30	2,690 2,450	35	2,940 2,690	45	3,220 2,940	35	4,490 4,090	45	4,940 4,490
35.1 ~42.0	30	2,090 1,900	35	2,280 2,090	45	2,510 2,280	30	2,820 2,570	35	3,080 2,820	45	3,380 3,080	35	5,120 4,660	45	5,620 5,120
42.1 ~48.0	35	2,610 2,380	45	2,850 2,610	55	3,140 2,850	35	3,550 3,230	45	3,880 3,550	55	4,260 3,880				
48.1 ~55.0	35	3,240 2,950	45	3,530 3,240	55	3,890 3,530	35	4,490 4,090	45	4,900 4,490	55	5,390 4,900				

ジグ用ブッシュ定価表

形式 d 内径	SDK・DRK(上段)				SEK・ERK(上段)				SFK・FRK(上段)			
	DK (下段)		EK (下段)		FK (下段)		FK (下段)		FK (下段)		FK (下段)	
	φ 長さ	単価	φ 長さ	単価	φ 長さ	単価	φ 長さ	単価	φ 長さ	単価	φ 長さ	単価
1.6 ~2.0	12	2,870		12	3,960		12	2,670				
		2,610			3,600			2,430				
2.1 ~3.0	12	2,380		12	3,270		12	2,180				
		2,160			2,970			1,980				
3.1 ~4.0	12	2,180	16 2,390	12	2,970	16 3,270	12	1,980	16 2,180			
		1,980	2,180		2,700	2,970		1,800	1,980			
4.1 ~6.0	12	2,080	16 2,290	12	2,870	16 3,150	12	1,880	16 2,060			
		1,890	2,080		2,610	2,870		1,710	1,880			
6.1 ~8.0	16	2,080	20 2,290	16	2,870	20 3,150	16	1,880	20 2,060			
		1,890	2,080		2,610	2,870		1,710	1,880			
8.1 ~10.0	16	2,080	20 2,290	16	2,870	20 3,150	16	1,880	20 2,060			
		1,890	2,080		2,610	2,870		1,710	1,880			
10.1 ~12.0	20	2,180	25 2,390	20	2,970	25 3,270	20	1,980	25 2,180			
		1,980	2,180		2,700	2,970		1,800	1,980			
12.1 ~15.0	20	2,480	25 2,720	20	3,470	25 3,810	20	2,280	25 2,500			
		2,250	2,480		3,150	3,470		2,070	2,280			
15.1 ~18.0	25	2,770	30 3,040	25	3,860	30 4,240	25	2,570	30 2,830			
		2,520	2,770		3,510	3,860		2,340	2,570			
18.1 ~22.0	25	3,340	30 3,680	25	4,600	30 5,050	25	3,140	30 3,450			
		3,040	3,340		4,180	4,600		2,850	3,140			
22.1 ~26.0	30	3,760	35 4,130	30	5,230	35 5,750	30	3,550	35 3,910			
		3,420	3,760		4,750	5,230		3,230	3,550			
26.1 ~30.0	30	4,490	35 4,940	30	6,270	35 6,900	30	4,290	35 4,710			
		4,090	4,490		5,700	6,270		3,900	4,290			
30.1 ~35.0	35	5,120	45 5,620	35	7,110	45 7,810	35	4,910	45 5,400			
		4,660	5,120		6,460	7,110		4,470	4,910			
35.1 ~42.0	35	5,750	45 6,320	35	8,050	45 8,850	35	5,540	45 6,090			
		5,230	5,750		7,320	8,050		5,040	5,540			

材質: SK-4又は同等材
 硬度: H.R.C60° 以上
 内径: 0.1mmとび高精度仕上
 外径: 内径基準の高精度仕上

止めねじ TK	
形式	単価
TK-5	120
TK-6	150
TK-8	180

止めがね RK	
形式	単価
RK-5	160
RK-6	190
RK-8	220

ショートタイプ SAK					ショートタイプ SBK				
内径	φ 長さ	単価	φ 長さ	単価	内径	φ 長さ	単価	φ 長さ	単価
2.0	4	1,280	6	1,280	2.0	4	1,950	6	1,950
3.0	4	1,150	6	1,150	3.0	4	1,670	6	1,670
4.0	6	1,000	8	1,000	4.0	6	1,400	8	1,400
5.0	6	900	8	900	5.0	6	1,280	8	1,280
6.0	6	900	8	900	6.0	6	1,280	8	1,280
8.0	8	900	10	900	8.0	8	1,280	10	1,280
10.0	8	900	10	900	10.0	8	1,280	10	1,280
12.0	10	1,000	12	1,000	12.0	10	1,420	12	1,420
13.0	10	1,150	12	1,150	13.0	10	1,540	12	1,540
16.0	16	1,280			16.0	16	1,800		
20.0	16	1,400			20.0	16	2,050		
25.0	20	1,530			25.0	20	2,320		

差込ブッシュ案内用 G K				
内径	φ 長さ	単価	φ 長さ	単価
8.0	12	770	16	850
10.0	12	770	16	850
12.0	16	880	20	960
15.0	16	990	20	1080
18.0	20	1,110	25	1220
22.0	20	1,220	25	1330
26.0	25	1,400	30	1540
30.0	25	1,520	30	1650
35.0	30	1,870	35	2040
42.0	30	2,090	35	2280
48.0	35	2,610	45	2850
55.0	35	3,240	45	3530