

## ジグ用ブッシュ定価表

形式 d 内径	SAK(上段) AK(下段)						SBK・BRK(上段) BK(下段)						SCK・CRK(上段) CK(下段)			
	ℓ 長さ	単価	ℓ 長さ	単価	ℓ 長さ	単価	ℓ 長さ	単価	ℓ 長さ	単価	ℓ 長さ	単価	ℓ 長さ	単価	ℓ 長さ	単価
0.8 ~1.0	6	1,970	8	2,160												
1.1 ~1.5	6	1,580	8	1,720												
1.6 ~2.0	8	1,450 1,310	10	1,580 1,430	12	1,720 1,550	8	2,010 1,810	10	2,190 1,980	12	2,400 2,160	12	3,230 2,910		
2.1 ~3.0	8	1,290 1,170	10	1,410 1,270	12	1,550 1,400	8	1,730 1,560	10	1,900 1,710	12	2,090 1,890	12	2,580 2,330		
3.1 ~4.0	10	1,060 960	12	1,160 1,050	16	1,260 1,140	10	1,470 1,330	12	1,610 1,450	16	1,780 1,610	12	2,140 1,930	16	2,340 2,110
4.1 ~6.0	10	930 840	12	1,020 920	16	1,120 1,010	10	1,340 1,210	12	1,470 1,330	16	1,610 1,450	12	2,020 1,820	16	2,220 2,000
6.1 ~8.0	12	930 840	16	1,020 920	20	1,120 1,010	12	1,340 1,210	16	1,470 1,330	20	1,610 1,450	16	2,020 1,820	20	2,220 2,000
8.1 ~10.0	12	930 840	16	1,020 920	20	1,120 1,010	12	1,340 1,210	16	1,470 1,330	20	1,610 1,450	16	2,020 1,820	20	2,220 2,000
10.1 ~12.0	16	1,060 960	20	1,160 1,050	25	1,260 1,140	16	1,470 1,330	20	1,610 1,450	25	1,780 1,610	20	2,140 1,930	25	2,340 2,110
12.1 ~15.0	16	1,190 1,080	20	1,300 1,170	25	1,430 1,290	16	1,600 1,440	20	1,760 1,590	25	1,920 1,730	20	2,380 2,150	25	2,620 2,360
15.1 ~18.0	20	1,340 1,210	25	1,470 1,330	30	1,600 1,440	20	1,860 1,680	25	2,040 1,840	30	2,240 2,020	25	2,740 2,470	30	3,000 2,700
18.1 ~22.0	20	1,470 1,330	25	1,600 1,440	30	1,770 1,600	20	2,130 1,920	25	2,330 2,100	30	2,560 2,310	25	3,390 3,060	30	3,720 3,350
22.1 ~26.0	25	1,680 1,520	30	1,850 1,670	35	2,030 1,830	25	2,540 2,290	30	2,780 2,510	35	3,050 2,750	30	3,890 3,510	35	4,280 3,860
26.1 ~30.0	25	1,830 1,650	30	1,980 1,790	35	2,190 1,980	25	2,810 2,530	30	3,080 2,780	35	3,380 3,050	30	4,650 4,190	35	5,100 4,590
30.1 ~35.0	30	2,250 2,030	35	2,450 2,210	45	2,690 2,430	30	3,230 2,910	35	3,530 3,180	45	3,870 3,490	35	5,390 4,860	45	5,930 5,340
35.1 ~42.0	30	2,720 2,450	35	2,970 2,680	45	3,270 2,950	30	3,390 3,060	35	3,700 3,330	45	4,060 3,660	35	6,150 5,540	45	6,750 6,080
42.1 ~48.0	35	3,400 3,060	45	3,710 3,340	55	4,090 3,690	35	4,260 3,840	45	4,660 4,200	55	5,120 4,610				
48.1 ~55.0	35	4,220 3,800	45	4,590 4,140	55	5,060 4,560	35	5,390 4,860	45	5,880 5,300	55	6,470 5,830				

## ジグ用ブッシュ定価表

形式 d 内径	SDK・DRK(上段) DK (下段)				SEK・ERK(上段) EK (下段)				SFK・FRK(上段) FK (下段)			
	φ	単価	φ	単価	φ	単価	φ	単価	φ	単価	φ	単価
	長さ		長さ		長さ		長さ		長さ		長さ	
1.6 ~2.0	12	3,740		12	5,150		12	3,480				
		3,370			4,640			3,140				
2.1 ~3.0	12	3,100		12	4,260		12	2,840				
		2,790			3,840			2,560				
3.1 ~4.0	12	2,620	16 2,870	12	3,570	16 3,930	12	2,380	16 2,620			
		2,360	2,590		3,220	3,540		2,150	2,360			
4.1 ~6.0	12	2,500	16 2,750	12	3,450	16 3,780	12	2,260	16 2,480			
		2,250	2,480		3,110	3,410		2,040	2,240			
6.1 ~8.0	16	2,500	20 2,750	16	3,450	20 3,780	16	2,260	20 2,480			
		2,250	2,480		3,110	3,410		2,040	2,240			
8.1 ~10.0	16	2,500	20 2,750	16	3,450	20 3,780	16	2,260	20 2,480			
		2,250	2,480		3,110	3,410		2,040	2,240			
10.1 ~12.0	20	2,620	25 2,870	20	3,570	25 3,930	20	2,380	25 2,620			
		2,360	2,590		3,220	3,540		2,150	2,360			
12.1 ~15.0	20	2,980	25 3,270	20	4,170	25 4,580	20	2,740	25 3,000			
		2,690	2,950		3,760	4,130		2,470	2,700			
15.1 ~18.0	25	3,330	30 3,650	25	4,640	30 5,090	25	3,090	30 3,400			
		3,000	3,290		4,180	4,590		2,790	3,060			
18.1 ~22.0	25	4,010	30 4,420	25	5,520	30 6,060	25	3,770	30 4,140			
		3,610	3,980		4,970	5,460		3,400	3,730			
22.1 ~26.0	30	4,520	35 4,960	30	6,280	35 6,900	30	4,260	35 4,700			
		4,070	4,470		5,660	6,210		3,840	4,230			
26.1 ~30.0	30	5,390	35 5,930	30	7,530	35 8,280	30	5,150	35 5,660			
		4,860	5,340		6,780	7,460		4,640	5,010			
30.1 ~35.0	35	6,150	45 6,750	35	8,540	45 9,380	35	5,900	45 6,480			
		5,540	6,080		7,690	8,450		5,310	5,840			
35.1 ~42.0	35	6,900	45 7,590	35	9,660	45 10,620	35	6,650	45 7,310			
		6,210	6,840		8,700	9,560		5,990	6,580			

材質:SK-4又は同等材

硬度:H.R.C60°以上

内径:0.1mmとび高精度仕上

外径:内径基準の高精度仕上

## 止めねじ TK

形式	単価
TK-5	150
TK-6	180
TK-8	220

## 止めがね RK

形式	単価
RK-5	200
RK-6	230
RK-8	270

## ショートタイプ SAK

ショートタイプ SAK					ショートタイプ SBK				
内径	φ	単価	φ	単価	内径	φ	単価	φ	単価
	長さ		長さ			長さ		長さ	
2.0	4	1,670	6	1,670	2.0	4	2,340	6	2,340
3.0	4	1,500	6	1,500	3.0	4	2,010	6	2,010
4.0	6	1,200	8	1,200	4.0	6	1,680	8	1,680
5.0	6	1,080	8	1,080	5.0	6	1,540	8	1,540
6.0	6	1,080	8	1,080	6.0	6	1,540	8	1,540
8.0	8	1,080	10	1,080	8.0	8	1,540	10	1,540
10.0	8	1,080	10	1,080	10.0	8	1,540	10	1,540
12.0	10	1,200	12	1,200	12.0	10	1,710	12	1,710
13.0	10	1,380	12	1,380	13.0	10	1,850	12	1,850
16.0	16	1,540			16.0	12	2,160	16	2,160
20.0	12	1,680	16	1,680	20.0	16	2,460		
25.0	16	1,840	20	1,840	25.0	20	2,790		

## 差込ブッシュ案内用 G K

差込ブッシュ案内用 G K				
内径	φ	単価	φ	単価
	長さ		長さ	
8.0	12	930	16	1020
10.0	12	930	16	1020
12.0	16	1,060	20	1160
15.0	16	1,190	20	1300
18.0	20	1,340	25	1470
22.0	20	1,470	25	1600
26.0	25	1,680	30	1850
30.0	25	1,830	30	1980
35.0	30	2,250	35	2450
42.0	30	2,720	35	2970
48.0	35	3,400	45	3710
55.0	35	4,220	45	4590